



CUBE-UV SPECIFICATIONS	CUBE-UV 500W & 1000 WATT	1000W
Input Voltage	110V-220V/60Hz/50HZ	
Timing mode	Wireless Remote Control Timing	
Remote control mode	Wireless wall access remote control	
Delay range	30 seconds delay start	
Wire length	6 feet, 25' extension cord included	
Lamp Voltage (v)	110±10	135±15
Lamp Current (w)	550	660
Warranty – Unit, Bulb	Unit: 1 year, Bulb: 6 months	
Base material	ABS	
Lamp size (mm) Height	894mm (35")	1199mm (44")
UVC Bulb Wavelength	254nm Germicidal WL	

CUBE-UV SPECIFICATIONS	500W & 1000 WATT	1000W
Pipe diameter (mm)	Φ19mm (7.4")	
UVC intensity@1meter	880uw/cm ²	1100uw/cm ²
Product size	300*300*1244(mm) (12"x12"x49")	300*300*1500(mm) (12"x12"x60")
Weight (g)	11,200 g. (25lb.)	12,200 g. (27lb.)
Bulb Lifetime	8000 hrs.	
Dielectric strength (V)	AC1500V	
Anti-electric shock Rate	CLASS1	
Color	Black	
Implement standard	EN 61199 EN 60901	
Working condition	-10°C - +45°C、 10% - 90% R.H.	
Storage Condition	-10°C - +45°C、 0% - 80% R.H.	
IP grade	IP20	
Package size (cm)	Center pillar: 100*20*27cm Base: 36*36*20cm	Center pillar : 132*20*27cm Base : 36*36*20cm
Package size (inches)	Center pillar: 39.4" x 7.9" x 10.6 in. Base: 14.2" x 14.2" x 7.9" in.	Center pillar: 51.2" x 7.9" x 10.6 in. Base: 14.2" x 14.2" x 7.9" in.
N.W	11.2KG - 25lb	12.2KG - 27lb.
G.W	12.2KG - 27lb	13.2KG - 29lb.
Outer Carton Size-cm	Pillar: 101*21*30cm Base: 37*37*38cm	Pillar: 133*21*30cm Base: 37*37*38cm

CUBE-UV Treatment Time	
Average	Wattage & Time
100 - 140 sq. meters	500w (15-30 minutes)
140 - 200 sq. meters	1000w (15-30minutes)
328' - 450 sq. ft. (18'x18') - (21'x21')	500w (15-30 minutes)
450' - 655 sq. ft. (21'x21') - (26'x26')	1000w (15-30minutes)

Copyright © 2021 MRSA-UV LLC All rights are reserved.

